

# GripTight MAX (GTMAX)

Hochdruck – Prüfverschlüsse

## Sichere Druckprüfung an Rohanystemen/Rohrenden



Durch den Hochdruck-Prüfverschluss GripTight™ der EST Group ist die Hochdruck-Rohrprüfung jetzt sicherer und einfacher als je zuvor. Im Gegensatz zu anderen Prüfstopfen, die sich lockern und herauslösen und zu gefährlichen Projektilen werden können, nutzt der GripTight™ Hochdruck-Prüfverschluss den Prüfdruck zur sicheren Verankerung und Abdichtung gegen die Rohrrinnenwand. Je größer der Druck, desto fester ist der halt!! Dies ermöglicht eine schnellere Installation, bessere Abdichtung und eine insgesamt höhere Prüfsicherheit. Betriebsdruck bis zu 15.000 psi (1034 bar). Erhältlich in Größen von 12,2 mm bis 610,0 mm. Größere Maße sind auf Anfrage verfügbar.

HD-Prüfleistungen, Eingesetzt bei Berstprüfungen unter Produktionsbedingungen. Ermöglicht sichere Tests bei hohen Drücken,

Prüfzeiten: Kein Schweißen oder Schneiden erforderlich. Schnellere Fabrikationsprüfung, bis zu 80 % Zeitersparnis bei der Prüfung.

Intelligenter Dichtungsaufbau: Geringer Dichtungsverschleiß bei hochwertiger Prüfleistung.

Positionierung durch Anschlagbund: Verhindert einen Verlust des Verschlusses im Rohrende.

Haltefeder: Gewährleistet die Retraktion der Greifsegmente. (Gripper).

Ersatzteile: Ersatzdichtungen & Gripper (Haltesystem) sind verfügbar und einfach auszutauschen.

Verfügbarkeit: Größen zwischen 12,2 mm (0,48 Zoll) und 609,6 mm (24 Zoll) in Shedule 40 und 80 (DN10 bis DN600) sind normalerweise auf Lager für den Versand am selben Tag oder zeitnah verfügbar.

Optionale Dichtungen: Flouroelastomer (Viton®\* oder gleichwertige Ausführung), Silikon, EPDM, Neopren.

Die einzigen Prüfstopfen, die mit einem Qualitätssicherungsprogramm nach ISO-9001 zertifiziert sind!

Erhältlich gemäß ANSI N45.2, 10CFR50 Anlage B

\*Viton® ist ein eingetragenes Warenzeichen von DuPont Dow Elastomers.

Zusätzlich dann noch mit einem Eignungsnachweis vom TÜV-Rheinland.

**CURTISS  
WRIGHT**  
**Flow Control Company**  
**EST Group**

**Table 1: GripTight MAX Single-Shaft Test Plug Specifications**

Part Number	Pipe Size and Schedule inches	Shaft Hex Size Across Flats inches	Hex Nut Size Across Flats inches	Functional ID Operating Range inches (mm)	Nominal Installation Torque ft-lbs (N-m)	Maximum Installation Torque ft-lbs (N-m)	NPT Size	Maximum Test Pressure PSIG (BARG)
GTMAX038P40	3/8" SCH 40	3/8	3/4	0.48 - 0.52 (12.2 - 13.2)	15 (20)	25 (34)	1/8	15000 (1034)
GTMAX050P160	1/2" SCH 160	3/8	3/4	0.48 - 0.52 (12.2 - 13.2)	15 (20)	25 (34)	1/8	15000 (1034)
GTMAX050P80	1/2" SCH 80	3/8	3/4	0.52 - 0.57 (13.2 - 14.5)	15 (20)	25 (34)	1/8	15000 (1034)
GTMAX050P40	1/2" SCH 40	3/8	3/4	0.57 - 0.63 (14.5 - 16.0)	15 (20)	25 (34)	1/8	15000 (1034)
GTMAX075P160	3/4" SCH 160	3/8	3/4	0.57 - 0.63 (14.5 - 16.0)	15 (20)	25 (34)	1/8	15000 (1034)
GTMAX1PXXS	1" SCH XXS	3/8	3/4	0.57 - 0.63 (14.5 - 16.0)	15 (20)	25 (34)	1/8	15000 (1034)
GTMAX050P10	1/2" SCH 10	3/8	3/4	0.63 - 0.69 (16.0 - 17.5)	15 (20)	25 (34)	1/8	15000 (1034)
GTMAX075P80	3/4" SCH 80	3/8	3/4	0.69 - 0.77 (17.5 - 19.6)	15 (20)	25 (34)	1/8	15000 (1034)
GTMAX075P40	3/4" SCH 40	3/8	3/4	0.77 - 0.85 (19.6 - 21.6)	25 (34)	40 (54)	1/8	15000 (1034)
GTMAX1P160	1" SCH 160	3/8	3/4	0.77 - 0.85 (19.6 - 21.6)	25 (34)	40 (54)	1/8	15000 (1034)
GTMAX075P10	3/4" SCH 10	3/8	3/4	0.85 - 0.93 (21.6 - 23.6)	25 (34)	40 (54)	1/8	15000 (1034)
GTMAX1P80	1" SCH 80	3/8	3/4	0.93 - 1.00 (23.6 - 25.4)	50 (68)	60 (81)	1/8	15000 (1034)
GTMAX1P40	1" SCH 40	3/8	3/4	1.01 - 1.09 (25.7 - 27.7)	50 (68)	60 (81)	1/8	15000 (1034)
GTMAX15PXXS	1-1/2" XXS	3/8	3/4	1.07 - 1.20 (27.2 - 30.5)	50 (68)	60 (81)	1/8	15000 (1034)
GTMAX1P10	1" SCH 10	3/8	3/4	1.07 - 1.20 (27.2 - 30.5)	50 (68)	60 (81)	1/8	15000 (1034)
GTMAX125P160	1-1/4" SCH 160	1/2	15/16	1.13 - 1.24 (28.7 - 31.5)	50 (68)	75 (102)	1/4	15000 (1034)
GTMAX1P5	1" SCH 5	1/2	15/16	1.13 - 1.24 (28.7 - 31.5)	50 (68)	75 (102)	1/4	15000 (1034)
GTMAX125P80	1-1/4" SCH 80	1/2	15/16	1.25 - 1.33 (31.8 - 33.8)	50 (68)	75 (102)	1/4	15000 (1034)
GTMAX125P40	1-1/4" SCH 40/STD	1/2	15/16	1.31 - 1.43 (33.3 - 36.3)	50 (68)	75 (102)	1/4	15000 (1034)
GTMAX15P160	1 1/2" SCH 160	1/2	15/16	1.31 - 1.43 (33.3 - 36.3)	50 (68)	75 (102)	1/4	15000 (1034)
GTMAX125P10	1 - 1/4" SCH 10	11/16	1 5/16	1.41 - 1.49 (35.8 - 37.8)	75 (102)	150 (204)	3/8	15000 (1034)
GTMAX125P5	1-1/4" SCH 5	11/16	1 5/16	1.47 - 1.61 (37.3 - 40.9)	75 (102)	150 (204)	3/8	15000 (1034)
GTMAX15P80	1-1/2" SCH 80	11/16	1 5/16	1.47 - 1.61 (37.3 - 40.9)	75 (102)	150 (204)	3/8	15000 (1034)
GTMAX2PXXS	2" XXS	11/16	1 5/16	1.47 - 1.61 (37.3 - 40.9)	75 (102)	150 (204)	3/8	15000 (1034)
GTMAX15P40	1-1/2" SCH 40/STD	11/16	1 5/16	1.58 - 1.66 (40.1 - 42.2)	75 (102)	150 (204)	3/8	15000 (1034)
GTMAX15P10	1-1/2" SCH 10	11/16	1 5/16	1.66 - 1.77 (42.2 - 45.0)	75 (102)	150 (204)	3/8	15000 (1034)
GTMAX2P160	2" SCH 160	11/16	1 5/16	1.66 - 1.77 (42.2 - 45.0)	75 (102)	150 (204)	3/8	15000 (1034)
GTMAX15P5	1-1/2" SCH 5	11/16	1 5/16	1.74 - 1.91 (44.2 - 48.5)	75 (102)	150 (204)	3/8	15000 (1034)
GTMAX25PXXS	2-1/2" XXS	11/16	1 5/16	1.74 - 1.91 (44.2 - 48.5)	75 (102)	150 (204)	3/8	15000 (1034)
GTMAX2P80	2" SCH 80/XS	11/16	1 5/16	1.91 - 1.99 (48.5 - 50.5)	75 (102)	150 (204)	3/8	12000 (827)
GTMAX198T		11/16	1 5/16	1.98 - 2.06 (50.3 - 52.3)	75 (102)	150 (204)	3/8	12000 (827)
GTMAX2P40	2" SCH 40/STD	11/16	1 5/16	2.04 - 2.12 (51.8 - 53.8)	75 (102)	150 (204)	3/8	12000 (827)
GTMAX2P10	2" SCH 10	11/16	1 5/16	2.10 - 2.22 (53.3 - 56.4)	75 (102)	150 (204)	3/8	12000 (827)
GTMAX25P160	2-1/2" SCH 160	11/16	1 5/16	2.10 - 2.22 (53.3 - 56.4)	75 (102)	150 (204)	3/8	12000 (827)
GTMAX2P5	2" SCH 5	11/16	1 5/16	2.22 - 2.30 (56.4 - 58.4)	75 (102)	150 (204)	3/8	12000 (827)
GTMAX25P80	2-1/2" SCH 80/XS	11/16	1 5/16	2.27 - 2.45 (57.7 - 62.2)	75 (102)	150 (204)	3/8	12000 (827)
GTMAX3PXXS	3" XXS	11/16	1 5/16	2.27 - 2.45 (57.7 - 62.2)	75 (102)	150 (204)	3/8	12000 (827)
GTMAX25P40	2-1/2" SCH 40/STD	1	1-7/8	2.44 - 2.54 (62.0 - 64.5)	150 (204)	300 (407)	1/2	12000 (827)
GTMAX253T		1	1-7/8	2.53 - 2.63 (64.3 - 66.8)	150 (204)	300 (407)	1/2	12000 (827)
GTMAX25P10	2-1/2" SCH 10	1	1-7/8	2.60 - 2.74 (65.9 - 69.6)	150 (204)	300 (407)	1/2	12000 (827)
GTMAX3P160	3" SCH 160	1	1-7/8	2.60 - 2.74 (65.9 - 69.6)	150 (204)	300 (407)	1/2	12000 (827)
GTMAX25P5	2"-1/2" SCH 5	1	1-7/8	2.68 - 2.78 (68.1 - 70.6)	150 (204)	300 (407)	1/2	12000 (827)
GTMAX35PXXS	3-1/2" XXS	1	1-7/8	2.70 - 2.89 (68.6 - 73.4)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX3P80	3" SCH 80/XS	1	1-7/8	2.87 - 2.98 (72.9 - 75.7)	150 (204)	300 (407)	1/2	12000 (827)
GTMAX296T		1	1-7/8	2.96 - 3.07 (75.2 - 78.0)	150 (204)	300 (407)	1/2	12000 (827)
GTMAX3P40	3" SCH 40/STD	1	1-7/8	3.04 - 3.14 (77.2 - 79.8)	150 (204)	300 (407)	1/2	12000 (827)



EST Group  
www.cw-estgroup.com

North, Central & South America  
EST Group Corporate Office  
2701 Township Line Road  
Hatfield, PA 19440-1770 USA  
P: +1.215.721.1100  
+1.800.355.7044  
F: +1.215.721.1101  
est-info@curtisswright.com

Europe / Middle East / Africa  
EST Group B.V.  
Hoom 312a  
2404 HL Alphen aan den Rijn  
The Netherlands  
P: +31.172.418841  
F: +31.172.418849  
est-emea@curtisswright.com

China  
P +86.400.636.5077  
est-china@curtisswright.cn

Singapore  
P +65.3158.5052  
est-asia@curtisswright.com

Part Number	Pipe Size and Schedule inches	Shaft Hex Size Across Flats inches	Hex Nut Size Across Flats inches	Functional ID Operating Range inches (mm)	Nominal Installation Torque ft-lbs (N-m)	Maximum Installation Torque ft-lbs (N-m)	NPT Size	Maximum Test Pressure PSIG (BARG)
GTMAX4PXXS	4" XXS	1	1-7/8	3.12 - 3.32 (79.2 - 84.3)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX3P10	3" SCH 10	1	1-7/8	3.23 - 3.34 (82.0 - 84.8)	150 (204)	300 (407)	1/2	12000 (827)
GTMAX3P5	3" SCH 5	1	1-7/8	3.30 - 3.41 (83.8 - 86.6)	150 (204)	300 (407)	1/2	12000 (827)
GTMAX35P80	3-1/2" SCH 80/XS	1	1-7/8	3.33 - 3.44 (84.6 - 87.4)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX4P160	4" SCH 160	1	1-7/8	3.41 - 3.57 (86.6 - 90.7)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX35P40	3-1/2" SCH 40/STD	1	1-7/8	3.52 - 3.63 (89.4 - 92.2)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX4P120	4" SCH 120	1	1-7/8	3.60 - 3.74 (91.4 - 95.0)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX35P10	3-1/2" SCH 10	1	1-7/8	3.73 - 3.84 (94.7 - 97.5)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX35P5	3-1/2" SCH 5	1	1-7/8	3.80 - 3.91 (96.5 - 99.3)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX4P80	4" SCH 80/XS	1	1-7/8	3.80 - 3.91 (96.5 - 99.3)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX390T		1	1-7/8	3.90 - 4.01 (99.1 - 101.9)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX4P40	4" SCH 40/STD	1	1-7/8	4.00 - 4.11 (101.6 - 104.4)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX5PXXS	5" XXS	1	1-7/8	4.03 - 4.25 (102.4 - 108.0)	150 (204)	300 (407)	1/2	8000 (552)
GTMAX4P10	4" SCH 10	1	1-7/8	4.23 - 4.34 (107.4 - 110.2)	150 (204)	300 (407)	1/2	10000 (689)
GTMAX4P5	4" SCH 5	1 1/4	2-1/4	4.28 - 4.47 (108.7 - 113.5)	200 (271)	380 (515)	3/4	10000 (689)
GTMAX5P160	5" SCH 160	1 1/4	2-1/4	4.28 - 4.47 (108.7 - 113.5)	200 (271)	380 (515)	3/4	10000 (689)
GTMAX442T		1 1/4	2-1/4	4.42 - 4.58 (112.3 - 116.3)	200 (271)	380 (515)	3/4	8000 (552)
GTMAX5P120	5" SCH 120	1 1/4	2-1/4	4.53 - 4.69 (115.1 - 119.1)	200 (271)	380 (515)	3/4	8000 (552)
GTMAX466T		1 1/4	2-1/4	4.66 - 4.82 (118.4 - 122.4)	200 (271)	380 (515)	3/4	8000 (552)
GTMAX5P80	5" SCH 80/XS	1 1/4	2-1/4	4.78 - 4.91 (121.4 - 124.7)	200 (271)	380 (515)	3/4	8000 (552)

Table 2: GripTight MAX Multi-Shaft Test Plug Specifications

Sales Part Number	Pipe Size and Schedule inches	Hex Nut Size Across Flats inches	Functional ID Range inches (mm)	Nominal Installation Torque ft-lbs (N-m)	Maximum Installation Torque ft-lbs (N-m)	NPT Size	Maximum Test Pressure PSIG (BARG)
GTMAX6PXXS	6" XXS	3/4	4.87 - 5.11 (123.7 - 129.8)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX5P40	5" SCH 40/STD	3/4	5.02 - 5.14 (127.5 - 130.6)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX514T		3/4	5.14 - 5.26 (130.6 - 133.6)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX6P160	6" SCH160	3/4	5.16 - 5.37 (131.1 - 136.4)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX5P10	5" SCH10	3/4	5.27 - 5.39 (133.9 - 136.9)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX5P5	5" SCH 5	3/4	5.32 - 5.44 (135.1 - 138.2)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX534T		3/4	5.34 - 5.51 (135.6 - 140.0)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX6P120	6" SCH120	3/4	5.47 - 5.64 (138.9 - 143.3)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX562T		3/4	5.62 - 5.76 (142.7 - 146.3)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX6P80	6" SCH 80/XS	3/4	5.73 - 5.87 (145.5 - 149.1)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX588T		3/4	5.88 - 6.03 (149.4 - 153.2)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX6P40	6" SCH 40/STD	3/4	6.04 - 6.17 (153.4 - 156.7)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX618T		3/4	6.18 - 6.32 (157.0 - 160.5)	35 (48)	55 (75)	1/2	8000 (552)
GTMAX6P10	6" SCH10	1 1/16	6.33 - 6.47 (160.8 - 164.3)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX6P5	6" SCH5	1 1/16	6.38 - 6.52 (162.1 - 165.6)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX653T		1 1/16	6.53 - 6.67 (165.9 - 169.4)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX668T		1 1/16	6.68 - 6.82 (169.7 - 173.2)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX8P160	8" SCH 160	1 1/16	6.78 - 7.04 (172.2 - 178.8)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX8PXXS	8" XXS	1 1/16	6.85 - 7.09 (174.0 - 180.1)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX8P140	8" SCH 140	1 1/16	6.97 - 7.20 (177.0 - 182.9)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX8P120	8" SCH 120	1 1/16	7.16 - 7.37 (181.9 - 187.2)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX730T		1 1/16	7.30 - 7.48 (185.4 - 190.0)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX8P100	8" SCH 100	1 1/16	7.41 - 7.59 (188.2 - 192.8)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX8P80	8" SCH 80/XS	1 1/16	7.60 - 7.75 (193.0 - 196.9)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX769T		1 1/16	7.69 - 7.84 (195.3 - 199.1)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX8P60	8" SCH 60	1 1/16	7.78 - 7.93 (197.6 - 201.4)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX787T		1 1/16	7.87 - 8.02 (199.9 - 203.7)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX8P40	8" SCH 40/STD	1 1/16	7.95 - 8.10 (201.9 - 205.7)	60 (81)	100 (136)	3/4	8000 (552)
GTMAX8P30	8" SCH 30	1 7/16	8.04 - 8.19 (204.2 - 208.0)	150 (202)	250 (340)	3/4	8000 (552)
GTMAX8P20	8" SCH 20	1 7/16	8.10 - 8.25 (205.7 - 209.6)	150 (202)	250 (340)	3/4	8000 (552)
GTMAX820T		1 7/16	8.20 - 8.35 (208.3 - 212.1)	150 (202)	250 (340)	3/4	8000 (552)
GTMAX8P10	8" SCH 10	1 7/16	8.30 - 8.45 (210.8 - 214.6)	150 (202)	250 (340)	3/4	8000 (552)
GTMAX8P5	8" SCH 5	1 7/16	8.38 - 8.53 (212.9 - 216.7)	150 (202)	250 (340)	3/4	8000 (552)
GTMAX10P160	10" SCH 160	1 7/16	8.45 - 8.91 (214.6 - 226.3)	150 (202)	250 (340)	3/4	6000 (414)
GTMAX10P140	10" SCH 140	1 7/16	8.70 - 9.16 (221.0 - 232.7)	150 (202)	250 (340)	3/4	6000 (414)
GTMAX10P120	10" SCH 120	1 7/16	9.01 - 9.47 (228.9 - 240.5)	150 (202)	250 (340)	3/4	6000 (414)



EST Group  
www.cw-estgroup.com

North, Central & South America  
EST Group Corporate Office  
2701 Township Line Road  
Hatfield, PA 19440-1770 USA  
P: +1.215.721.1100  
+1.800.355.7044  
F: +1.215.721.1101  
est-info@curtisswright.com

Europe / Middle East / Africa  
EST Group B.V.  
Hoom 312a  
2404 HL Alphen aan den Rijn  
The Netherlands  
P: +31.172.418841  
F: +31.172.418849  
est-emea@curtisswright.com

China  
P +86.400.636.5077  
est-china@curtisswright.cn

Singapore  
P +65.3158.5052  
est-asia@curtisswright.com

**Table 3: GripTight MAX Vent Cap Selection Guide**

Pipe Size NPS (DN)	SCH 5	SCH 10	STD	SCH40	XS	SCH80	SCH120	SCH160	XXS
3/8 (10)	*	*	*	*	*	*	*	*	*
1/2 (15)	*	*	*	*	*	*	*	*	*
3/4 (20)	*	*	*	*	*	*	*	*	*
1 (25)	*	*	*	*	*	*	*	*	*
1-1/4 (32)	GTVc-0088	GTVc-0088	*	*	*	*	*	*	*
1-1/2 (40)	GTVc-0088	GTVc-0088	GTVc-0088	GTVc-0088	GTVc-0088	GTVc-0088	*	*	*
2 (50)	GTVc-0088	GTVc-0088	GTVc-0088	GTVc-0088	GTVc-0088	GTVc-0088	*	GTVc-0088	GTVc-0088
2-1/2 (65)	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0088	GTVs-0088	*	GTVc-0088	GTVc-0088
3 (80)	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	*	GTVc-0125	GTVc-0088
3-1/2 (90)	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	*	*	GTVc-0125
4 (100)	GTVc-0150	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125	GTVc-0125
5 (125)	**	**	**	**	GTVc-0150	GTVc-0150	GTVc-0150	GTVc-0150	GTVc-0125
6 (150)	**	**	**	**	**	**	**	**	**
8 (200) 10 (250)	**	**	**	**	**	**	**	**	**

\*GripTight Vent Caps not available due to small pipe / tube ID's and space restrictions.

\*\* Multi-Shaft GTMAX Test Plugs with cast Far Supports have integrated vents. For Multi-Shaft GTMAX Test Plugs with machined Far Supports, use Vent Cap GTVC-0075

**Table 4: Replacement Parts and Accessories for Standard NPS Size GripTight MAX Test Plugs**

GTMAX Part Number	Replacement Gripper Assembly (Includes Spring)	Replacement Seal	Replacement Spring	Safety Gag	High Pressure Cap
GTMAX-038P40	GTMAX-038P40-GR	GTMAX-038P40-URS	GTMAX-038P40-SPR	SFG-0038	M00281
GTMAX-050P80	GTMAX-050P80-GR	GTMAX-050P80-URS	GTMAX-050P80-SPR	SFG-0050	M00281
GTMAX-050P40	GTMAX-050P40-GR	GTMAX-050P40-URS	GTMAX-050P40-SPR	SFG-0050	M00281
GTMAX-075P160	GTMAX-075P160-GR	GTMAX-075P160-URS	GTMAX-075P160-SPR	SFG-0075	M00281
GTMAX-1PXXS	GTMAX-1PXXS-GR	GTMAX-1PXXS-URS	GTMAX-1PXXS-SPR	SFG-0100	M00281
GTMAX-050P10	GTMAX-050P10-GR	GTMAX-050P10-URS	GTMAX-050P10-SPR	SFG-0050	M00281
GTMAX-075P80	GTMAX-075P80-GR	GTMAX-075P80-URS	GTMAX-075P80-SPR	SFG-0075	M00281
GTMAX-075P40	GTMAX-075P40-GR	GTMAX-075P40-URS	GTMAX-075P40-SPR	SFG-0075	M00281
GTMAX-075P10	GTMAX-075P10-GR	GTMAX-075P10-URS	GTMAX-075P10-SPR	SFG-0075	M00281
GTMAX-1P160	GTMAX-1P160-GR	GTMAX-1P160-URS	GTMAX-1P160-SPR	SFG-0100	M00281
GTMAX-1P80	GTMAX-1P80-GR	GTMAX-1P80-URS	GTMAX-1P80-SPR	SFG-0100	M00281
GTMAX-1P40	GTMAX-1P40-GR	GTMAX-1P40-URS	GTMAX-1P40-SPR	SFG-0100	M00281
GTMAX-1P10	GTMAX-1P10-GR	GTMAX-1P10-URS	GTMAX-1P10-SPR	SFG-0100	M00281
GTMAX-15PXXS	GTMAX-15PXXS-GR	GTMAX-15PXXS-URS	GTMAX-15PXXS-SPR	SFG-0150	M00281
GTMAX-1P5	GTMAX-1P5-GR	GTMAX-1P5-URS	GTMAX-1P5-SPR	SFG-0100	M00282
GTMAX-125P160	GTMAX-125P160-GR	GTMAX-125P160-URS	GTMAX-125P160-SPR	SFG-0125	M00282
GTMAX-125P80	GTMAX-125P80-GR	GTMAX-125P80-URS	GTMAX-125P80-SPR	SFG-0125	M00282
GTMAX-125P40	GTMAX-125P40-GR	GTMAX-125P40-URS	GTMAX-125P40-SPR	SFG-0125	M00282
GTMAX-15P160	GTMAX-15P160-GR	GTMAX-15P160-URS	GTMAX-15P160-SPR	SFG-0150	M00282
GTMAX-125P10	GTMAX-125P10-GR	GTMAX-125P10-URS	GTMAX-125P10-SPR	SFG-0125	M00283
GTMAX-125P5	GTMAX-125P5-GR	GTMAX-125P5-URS	GTMAX-125P5-SPR	SFG-0125	M00283
GTMAX-15P80	GTMAX-15P80-GR	GTMAX-15P80-URS	GTMAX-15P80-SPR	SFG-0150	M00283



EST Group  
[www.cw-estgroup.com](http://www.cw-estgroup.com)

**North, Central & South America**  
EST Group Corporate Office  
2701 Township Line Road  
Hatfield, PA 19440-1770 USA  
P: +1.215.721.1100  
+1.800.355.7044  
F: +1.215.721.1101  
[est-info@curtisswright.com](mailto:est-info@curtisswright.com)

**Europe / Middle East / Africa**  
EST Group B.V.  
Hoon 312a  
2404 HL Alphen aan den Rijn  
The Netherlands  
P: +31.172.418841  
F: +31.172.418849  
[est-emea@curtisswright.com](mailto:est-emea@curtisswright.com)

**China**  
P +86.400.636.5077  
[est-china@curtisswright.cn](mailto:est-china@curtisswright.cn)

**Singapore**  
P +65.3158.5052  
[est-asia@curtisswright.com](mailto:est-asia@curtisswright.com)

GTMAX Part Number	Replacement Gripper Assembly (Includes Spring)	Replacement Seal	Replacement Spring	Safety Gag	High Pressure Cap
GTMAX-2PXXS	GTMAX-2PXXS-GR	GTMAX-2PXXS-URS	GTMAX-2PXXS-SPR	SFG-0200	M00283
GTMAX-15P40	GTMAX-15P40-GR	GTMAX-15P40-URS	GTMAX-15P40-SPR	SFG-0150	M00283
GTMAX-15P10	GTMAX-15P10-GR	GTMAX-15P10-URS	GTMAX-15P10-SPR	SFG-0150	M00283
GTMAX-2P160	GTMAX-2P160-GR	GTMAX-2P160-URS	GTMAX-2P160-SPR	SFG-0200	M00283
GTMAX-15P5	GTMAX-15P5-GR	GTMAX-15P5-URS	GTMAX-15P5-SPR	SFG-0150	M00283
GTMAX-25PXXS	GTMAX-25PXXS-GR	GTMAX-25PXXS-URS	GTMAX-25PXXS-SPR	SFG-0250	M00283
GTMAX-2P80	GTMAX-2P80-GR	GTMAX-2P80-URS	GTMAX-2P80-SPR	SFG-0200	M00283
GTMAX-2P40	GTMAX-2P40-GR	GTMAX-2P40-URS	GTMAX-2P40-SPR	SFG-0200	M00283
GTMAX-2P10	GTMAX-2P10-GR	GTMAX-2P10-URS	GTMAX-2P10-SPR	SFG-0200	M00283
GTMAX-25P160	GTMAX-25P160-GR	GTMAX-25P160-URS	GTMAX-25P160-SPR	SFG-0250	M00283
GTMAX-2P5	GTMAX-2P5-GR	GTMAX-2P5-URS	GTMAX-2P5-SPR	SFG-0200	M00283
GTMAX-25P80	GTMAX-25P80-GR	GTMAX-25P80-URS	GTMAX-25P80-SPR	SFG-0250	M00283
GTMAX-3PXXS	GTMAX-3PXXS-GR	GTMAX-3PXXS-URS	GTMAX-3PXXS-SPR	SFG-0300	M00283
GTMAX-25P40	GTMAX-25P40-GR	GTMAX-25P40-URS	GTMAX-25P40-SPR	SFG-0250	M00284
GTMAX-25P10	GTMAX-25P10-GR	GTMAX-25P10-URS	GTMAX-25P10-SPR	SFG-0250	M00284
GTMAX-3P160	GTMAX-3P160-GR	GTMAX-3P160-URS	GTMAX-3P160-SPR	SFG-0300	M00284
GTMAX-25P5	GTMAX-25P5-GR	GTMAX-25P5-URS	GTMAX-25P5-SPR	SFG-0250	M00284
GTMAX-35PXXS	GTMAX-35PXXS-GR	GTMAX-35PXXS-URS	GTMAX-35PXXS-SPR	SFG-0350	M00284
GTMAX-3P80	GTMAX-3P80-GR	GTMAX-3P80-URS	GTMAX-3P80-SPR	SFG-0300	M00284
GTMAX-3P40	GTMAX-3P40-GR	GTMAX-3P40-URS	GTMAX-3P40-SPR	SFG-0300	M00284
GTMAX-4PXXS	GTMAX-4PXXS-GR	GTMAX-4PXXS-URS	GTMAX-4PXXS-SPR	SFG-0400	M00284
GTMAX-3P10	GTMAX-3P10-GR	GTMAX-3P10-URS	GTMAX-3P10-SPR	SFG-0300	M00284
GTMAX-3P5	GTMAX-3P5-GR	GTMAX-3P5-URS	GTMAX-3P5-SPR	SFG-0300	M00284
GTMAX-35P80	GTMAX-35P80-GR	GTMAX-35P80-URS	GTMAX-35P80-SPR	SFG-0350	M00284
GTMAX-4P160	GTMAX-4P160-GR	GTMAX-4P160-URS	GTMAX-4P160-SPR	SFG-0400	M00284
GTMAX-35P40	GTMAX-35P40-GR	GTMAX-35P40-URS	GTMAX-35P40-SPR	SFG-0350	M00284
GTMAX-4P120	GTMAX-4P120-GR	GTMAX-4P120-URS	GTMAX-4P120-SPR	SFG-0400	M00284
GTMAX-35P10	GTMAX-35P10-GR	GTMAX-35P10-URS	GTMAX-35P10-SPR	SFG-0350	M00284
GTMAX-35P5	GTMAX-35P5-GR	GTMAX-35P5-URS	GTMAX-35P5-SPR	SFG-0350	M00284
GTMAX-4P80	GTMAX-4P80-GR	GTMAX-4P80-URS	GTMAX-4P80-SPR	SFG-0400	M00284
GTMAX-4P40	GTMAX-4P40-GR	GTMAX-4P40-URS	GTMAX-4P40-SPR	SFG-0400	M00284
GTMAX-5PXXS	GTMAX-5PXXS-GR	GTMAX-5PXXS-URS	GTMAX-5PXXS-SPR	SFG-0500	M00284
GTMAX-4P10	GTMAX-4P10-GR	GTMAX-4P10-URS	GTMAX-4P10-SPR	SFG-0400	M00284
GTMAX-4P5	GTMAX-4P5-GR	GTMAX-4P5-NRS	GTMAX-4P5-SPR	SFG-0400	M00285
GTMAX-5P160	GTMAX-5P160-GR	GTMAX-5P160-NRS	GTMAX-5P160-SPR	SFG-0500	M00285
GTMAX-5P120	GTMAX-5P120-GR	GTMAX-5P120-NRS	GTMAX-5P120-SPR	SFG-0500	M00285
GTMAX-5P80	GTMAX-5P80-GR	GTMAX-5P80-NRS	GTMAX-5P80-SPR	SFG-0500	M00285
GTMAX-6PXXS	GTMAX-6PXXS-GR	GTMAX-6PXXS-URS	GTMAX-6PXXS-SPR	SFG-0600	M00284
GTMAX-5P40	GTMAX-5P40-GR	GTMAX-5P40-URS	GTMAX-5P40-SPR	SFG-0500	M00284
GTMAX-6P160	GTMAX-6P160-GR	GTMAX-6P160-URS	GTMAX-6P160-SPR	SFG-0600	M00284
GTMAX-5P10	GTMAX-5P10-GR	GTMAX-5P10-URS	GTMAX-5P10-SPR	SFG-0500	M00284
GTMAX-5P5	GTMAX-5P5-GR	GTMAX-5P5-URS	GTMAX-5P5-SPR	SFG-0500	M00284



EST Group  
[www.cw-estgroup.com](http://www.cw-estgroup.com)

**North, Central & South America**  
**EST Group Corporate Office**  
 2701 Township Line Road  
 Hatfield, PA 19440-1770 USA  
 P: +1.215.721.1100  
 +1.800.355.7044  
 F: +1.215.721.1101  
[est-info@curtisswright.com](mailto:est-info@curtisswright.com)

**Europe / Middle East / Africa**  
**EST Group B.V.**  
 Hoorn 312a  
 2404 HL Alphen aan den Rijn  
 The Netherlands  
 P: +31.172.418841  
 F: +31.172.418849  
[est-emea@curtisswright.com](mailto:est-emea@curtisswright.com)

**China**  
 P +86.400.636.5077  
[est-china@curtisswright.cn](mailto:est-china@curtisswright.cn)

**Singapore**  
 P +65.3158.5052  
[est-asia@curtisswright.com](mailto:est-asia@curtisswright.com)

GTMAX Part Number	Replacement Gripper Assembly (Includes Spring)	Replacement Seal	Replacement Spring	Safety Gag	High Pressure Cap
GTMAX-6P120	GTMAX-6P120-GR	GTMAX-6P120-URS	GTMAX-6P120-SPR	SFG-0600	M00284
GTMAX-6P80	GTMAX-6P80-GR	GTMAX-6P80-URS	GTMAX-6P80-SPR	SFG-0600	M00284
GTMAX-6P40	GTMAX-6P40-GR	GTMAX-6P40-URS	GTMAX-6P40-SPR	SFG-0600	M00284
GTMAX-6P10	GTMAX-6P10-GR	GTMAX-6P10-URS	GTMAX-6P10-SPR	SFG-0600	M00285
GTMAX-6P5	GTMAX-6P5-GR	GTMAX-6P5-URS	GTMAX-6P5-SPR	SFG-0600	M00285
GTMAX-8P160	GTMAX-8P160-GR	GTMAX-8P160-URS	GTMAX-8P160-SPR	SFG-0800	M00285
GTMAX-8PXXS	GTMAX-8PXXS-GR	GTMAX-8PXXS-URS	GTMAX-8PXXS-SPR	SFG-0800	M00285
GTMAX-8P140	GTMAX-8P140-GR	GTMAX-8P140-URS	GTMAX-8P140-SPR	SFG-0800	M00285
GTMAX-8P120	GTMAX-8P120-GR	GTMAX-8P120-URS	GTMAX-8P120-SPR	SFG-0800	M00285
GTMAX-8P100	GTMAX-8P100-GR	GTMAX-8P100-URS	GTMAX-8P100-SPR	SFG-0800	M00285
GTMAX-8P80	GTMAX-8P80-GR	GTMAX-8P80-URS	GTMAX-8P80-SPR	SFG-0800	M00285
GTMAX-8P60	GTMAX-8P60-GR	GTMAX-8P60-URS	GTMAX-8P60-SPR	SFG-0800	M00285
GTMAX-8P40	GTMAX-8P40-GR	GTMAX-8P40-URS	GTMAX-8P40-SPR	SFG-0800	M00285
GTMAX-8P30	GTMAX-8P30-GR	GTMAX-8P30-URS	GTMAX-8P30-SPR	SFG-0800	M00285
GTMAX-8P20	GTMAX-8P20-GR	GTMAX-8P20-URS	GTMAX-8P20-SPR	SFG-0800	M00285
GTMAX-8P10	GTMAX-8P10-GR	GTMAX-8P10-URS	GTMAX-8P10-SPR	SFG-0800	M00285
GTMAX-8P5	GTMAX-8P5-GR	GTMAX-8P5-URS	GTMAX-8P5-SPR	SFG-0800	M00285
GTMAX-10P160	GTMAX-10P160-GR	GTMAX-10P160-URS	GTMAX-10P160-SPR	SFG-1000	M00285
GTMAX-10P140	GTMAX-10P140-GR	GTMAX-10P140-URS	GTMAX-10P140-SPR	SFG-1000	M00285
GTMAX-10P120	GTMAX-10P120-GR	GTMAX-10P120-URS	GTMAX-10P120-SPR	SFG-1000	M00285

Note: Replacement parts and accessories are available for all GripTight MAX Test Plugs. Contact EST Group Customer Service for more information.



EST Group  
[www.cw-estgroup.com](http://www.cw-estgroup.com)

**North, Central & South America**  
**EST Group Corporate Office**  
 2701 Township Line Road  
 Hatfield, PA 19440-1770 USA  
 P: +1.215.721.1100  
 +1.800.355.7044  
 F: +1.215.721.1101  
[est-info@curtisswright.com](mailto:est-info@curtisswright.com)

**Europe / Middle East / Africa**  
**EST Group B.V.**  
 Hoorn 312a  
 2404 HL Alphen aan den Rijn  
 The Netherlands  
 P: +31.172.418841  
 F: +31.172.418849  
[est-emea@curtisswright.com](mailto:est-emea@curtisswright.com)

**China**  
 P +86.400.636.5077  
[est-china@curtisswright.cn](mailto:est-china@curtisswright.cn)

**Singapore**  
 P +65.3158.5052  
[est-asia@curtisswright.com](mailto:est-asia@curtisswright.com)